



Sturt Highway Paringa
Ph (08) 8595 5388
www.hoodsagrimotive.com.au



MK 3 – 5 ROW UNIVERSAL SEEDER BAR

25' to 60' WORKING WIDTHS – 7, 8, 9, 10 & 12" TYNE SPACING
 800mm (31.5") Underframe clearance – Fully floating hitch
 Hydraulic or spring tynes – Adjustable to 450lbs



VINEYARD SEEDER – DISC or TYNE
 10 ROW – 1.8m SOWING WIDTH
 Optional: Small Seeds Box & Finger Harrows



Grow a Better Crop



HEAVY DUTY HANDCULT
 12 TYNE 1.92m
 16 TYNE 2.56m
 2 & 4 TYNE EXTENSIONS AVAILABLE
 Optional: 620 Tynes Available



FOLDING WING HYDRAULIC TRASHWORKER

FEATURES - Four (4) row main frame - Edge-on tyne 50mm x 32mm (2" x 1 3/4") - Robust 100mm x 100mm main frame - Hydraulic tyne loading - Tyne Spacings: 305mm (12") or 254mm (10") - Tyne breakout, up to 454kgs (1,000lbs) - 770mm underframe clearance - Induction hardend pins (35mm) and bushes - Maximum working depth, 360mm

SPACING BETWEEN ROWS - One and Two: 770mm - Two and Three and Three and Four: 950mm



UNIVERSAL TRASHWORKER

10", 12" & 13.1" SPACINGS – 29', 35' & 41' WORKING WIDTHS

FEATURES - Tyne spacings of 254mm (10") - 300mm (12") and 333mm (13.1") - Front castoring wheels - 5 rows, 100x100mm RHS - 5-2m (17') fully floating hitch - Centre section; 9mm section on front and rear beams - Tyne assembly, breakout adjustable to 455kgs / 1000lbs - Depth gauge - Safety chains - Tyne foot bolt hole centres, 57mm and 15mm - 20 litre gas accumulator on all sizes - Centre tyres; 16/70 x 20 x 14ply 'Sure Grip' - Optional 2,4 and 6 tyne extensions - Centre section, wheel centres 4.0m - Depth control; Rock-shaft with tandem cylinders mechanically linked to wing wheels

SPACING BETWEEN ROWS - One and Two: 705mm - Two and Three, Three and Four and Four and Five: 765mm

BUILDING QUALITY MACHINERY SINCE 1904 AT KILKENNY